STANDARD NOTES FOR EROSION CONTROL PLAN (CONTINUED)

17. ALL POLLUTANTS THAT OCCUR DURING CONSTRUCTION SHALL BE HANDLED AND DISPOSED OF IN A MANNER THAT DOES NOT CAUSE CONTAMINATION OF STORM WATER.

18. ALL EROSION AND SEDIMENT CONTROL BMPS SHALL BE REGULARLY INSPECTED, MAINTAINED, AND REPAIRED AS NEEDED BY THE PROPERTY OWNER OR PERMIT HOLDER TO ENSURE CONTINUED PERFORMANCE OF THEIR INTENDED FUNCTION. A MAINTENANCE LOG SHALL BE PROVIDED AND KEPT AS PERMANENT RECORD. THE MAINTENANCE LOG SHALL BE IN A DESIGNATED ON-SITE LOCATION. INSPECT ONCE DAILY ON ACTIVE SITES, ONCE EVERY TWO WEEKS ON INACTIVE SITES, AND WITHIN 24 HOURS FOLLOWING A 0.5 INCH RAIN EVENT.

19. ALL CONSTRUCTION ACTIVITIES SHALL BE SUPERVISED BY AN INDIVIDUAL WHO SHALL HAVE SUCCESSFULLY COMPLETED FORMAL TRAINING IN EROSION AND SEDIMENT CONTROL DURING CONSTRUCTION BY A RECOGNIZED ORGANIZATION ACCEPTABLE TO THE CITY. A CERTIFICATION OR SUFFICIENT EVIDENCE OF SUCCESSFUL COMPLETION OF SUCH TRAINING SHALL BE SUBMITTED PRIOR TO CONSTRUCTION.

20. ALL TEMPORARY BMP'S SHALL BE REMOVED WITHIN 30 DAYS AFTER FINAL SITE STABILIZATION IS ACHIEVED.

21. CONSTRUCTION SHALL NOT BE CONSIDERED COMPLETE AND ACCEPTABLE UNTIL ALL DISTURBED SOIL SURFACES HAVE BEEN PROTECTED FROM EROSION.

22. VEGETATED STABILIZATION AND LANDSCAPING SHALL BE FERTILIZED, WATERED AND MAINTAINED TO ENSURE THAT GROWTH OF VEGETATION IS ESTABLISHED AND SUSTAINED.

23. DURING DRY WEATHER CONSTRUCTION PERIODS THE CONTRACTOR SHALL PROVIDE PROJECT-SPECIFIC DUST CONTROL MEASURES. THE CONTRACTOR SHALL MAINTAIN THE DUST CONTROL MEASURES THROUGH DRY WEATHER PERIODS UNTIL ALL DISTURBED AREAS HAVE BEEN STABILIZED. IMMEDIATELY RE-STABILIZE AREAS DISTURBED BY CONTRACTOR'S OPERATIONS OR OTHER ACTIVITIES (WIND, WATER, VANDALISM, ETC.).

24. ENTRY ONTO THE CONSTRUCTION SITE SHALL BE RESTRICTED TO A SINGLE APPROVED ENTRANCE AS SHOWN ON THE PLAN.

25. MAINTENANCE AND REPAIR OF HEAVY EQUIPMENT AND VEHICLES WHICH INVOLVE POTENTIAL CONTAMINANTS (OIL, SOLVENTS, HYDRAULIC FLUID, ETC.) MUST BE CONDUCTED IN A MANNER WHICH PREVENTS CONTAMINATION OF SOILS, SURFACE WATER AND GROUND WATER. TARPS, DRIP PANS, OR OTHER APPROPRIATE MEASURES SHALL BE USED AS NECESSARY.

26. STRIPPING, TOPSOIL, AND UNSUITABLE MATERIAL STOCKPILES SHALL BE HYDROSEEDED. MAINTENANCE OF STOCKPILE AREAS AND REAPPLICATION OF HYDROSEED COVERING SHALL BE REQUIRED IF BARE SOIL IS PRESENT.

TEMPORARY EROSION CONTROL SEED MIX

	% WEIGHT	% PURITY	% GERMINATION
CHEWINGS OR ANNUAL BLUE GRASS *FESTUCA RUBRA VAR. COMMUTATA OR POA ANNA*	40	98	90
PERENNIAL RYE – *LOLIUM PERENNE*	50	98	90
REDTOP OR COLONIAL BENTGRASS *AGROSTIS ALBA* OR *AGROSTIS TENUIS*	5	92	85
WHITE DUTCH CLOVER *TRIFOLIUM REPENS*	5	98	90

27. THE CONTRACTOR SHALL REMOVE ALL ACCUMULATED SEDIMENT FROM THE CATCH BASINS, DRYWELLS, UTILITY TRENCHES, AND STORM PIPES PRIOR TO ACCEPTANCE BY THE CITY.

EROSION CONTROL GENERAL NOTES

STANDARD DETAIL

THE CITY OF BATTLE GROUND

CITY OF BATTLE GROUND
APPROVED

Mark Henry 06/11/2018

CITY ENGINEER DATE

REVISIONS:	DATE:	DRAWN:	DESIGNED:
1	8/12/98	BSG	GGH
2	8/30/05	ALL	ALL
3	9/15/10	RMJ	RMJ
4	3/06/17	CAS	KDU

EC-1.00B