



NOTES:

1. INSTALL WATTLES BEHIND CURB IN 5' SIDEWALK CATCHMENT AREA OR PLANTER STRIP.
2. WATTLE SHALL BE CONSTRUCTED IN ACCORDANCE WITH WSDOT STD. SPEC. 9-14.5(5).
3. WATTLE SHALL BE INSPECTED REGULARLY, AND IMMEDIATELY AFTER A RUNOFF PRODUCING RAINFALL, TO ENSURE THEY REMAIN THOROUGHLY ENTRENCHED AND IN CONTACT WITH THE SOIL.
4. SEDIMENT BUILDUP IN EXCESS OF 4 INCHES IS TO BE REMOVED.
5. INSTALL WATTLE SNUGLY AGAINST THE BACK OF THE CURB USING 1"X1" FIR OR PINE STAKE. ABUT ADJACENT WATTLE TIGHTLY, END TO END, WITHOUT OVERLAPPING THE ENDS.
6. PILOT HOLES MAY BE DRIVEN THROUGH THE WATTLE AND INTO THE SOIL, WHEN SOIL CONDITIONS REQUIRE.

N.T.S.

STRAW WATTLES BEHIND CURB

STANDARD
DETAIL



CITY OF BATTLE GROUND
APPROVED

Mark Heneg

06/11/2018

CITY ENGINEER

DATE

REVISIONS:	DATE:	DRAWN:	DESIGNED:
1	03/02/17	KDU	KDU
2	3/13/17	CAS	KDU

EC-6.05